


grandMA ultra-light

- top class for smaller shows

The grandMA ultra-light is a reduced version of the grandMA light console that has all of the software features of the larger consoles. It is completely compatible with the grandMA family. The grandMA ultra-light brings all the user programmability of a top of the line console to some of the smallest shows. High-end features such as multi-user programming are also included with the grandMA ultra-light, making it the perfect console for professional programmers working on smaller or budget constrained productions.

Technical Specification - Art.-No. 120303



Protocols: DMX-512A, MA-Net, Art-Net, Pathport, Portall, Strand Shownet, Midi Show Control, ACN-

ready

Parameters: 2,048

(up to 16,384 with Parameter Expansion

via NSPs)

Cues: virtual unlimited Sequences: 999 Effects: 899 Groups: 999 Presets: 8,991

Dimmer Profiles: virtuel unlimited

User Profiles: 32

User Interface (Hardware)

Executor Faders: 10 manually operated

Executor Buttons: 20 Rotary Encoders: 4 Trackball: 1 (integrated)

User Interface (Software)

Playback Fader: 10 x 128 pages

Playback Fader Buttons: 20 x 128 pages *Playback Buttons :* 20 x 128 pages

Physical Input / Output

Network: 100 base TX, RJ45 (EtherCon on request)
DMX-512A: 2x OUT, 1x IN MIDI: 1x OUT, 1x IN,

Time Code: 1x SMPTE (LTC, MTC) *RS232:* 2x DB-9 (restricted)

Keyboard: 1x PS2 *Mouse:* 1x PS2

Printer Port: 1x parallel

VGA: 2x DB-15



USB: 2x USB

DC-Remote: 1x DB-25

Sound Input: 1x 6.3mm jack (sym.)

Displays

Internal Screen: 1x TFT Touchscreen

External Screen: 1 VGA + 1 (same as internal)

Dimensions

Size: 635 x 157 x 490 mm (25 x 6.2 x 19.3 inches) **Weight:** 12.9 kg / 28.5 lbs

System

Operating System: VxWorks Main Board CPU: VIA, 800MHz Main Memory: 256MB Hard Drive: 20GB minimum

Floppy Drive: 1.44MB

Power Supply: 90-230V, 50-60Hz, 100VA


Advanced Features


- Max. 16 consoles networked as Multi User, offering virtual partitioned areas ("Worlds")
- consoles in the same session are automatically a backup system
- Max. 64 DMX universes with 16 NSPs
- Auto-Save function
- Oops function (undo up to 20 commands)
- Recall commands direct from command line
- Supports 6 PDA remotes via Wireless LAN
- FTP file server support and remote file backup
- Complete suite of accessory PC software
- grandMA the DVD interactive training DVD

complete with tutorials

Detailed Software Features

- Multi-User programming
- "Worlds" feature provides virtual partitions between control areas for different users
- Full Tracking Backup between consoles
- Playback tracking for up to 16 consoles
- Sophisticated Effects generation
- Automatic chase creation with MATricks
- Fixture replacement while preserving programming
- Automatic cloning of additional fixtures or ranges of fixtures extends throughout all cues and presets in the show
- Auto-Save
- Partial show read
- Color Picker visual color selector
- Gobo thumbnails appear on preset keys
- Matrix programming with imported bitmaps
- Multiple user profiles and logins (at various security levels)
- Integrated wire frame visualizer
- Stage movement in XYZ coordinates
- Blind Editing & Blind Programmer
- ASCII Show Read / Write
- DMX IN or Art-Net IN
- Virtual Playback





Parameter Expansion

Large shows may require more control channels than a single console can handle. Instead of virtually linking the outputs of multiple consoles, grandMA offers true expansion of a single console's parameter capacity. Up to 16,384 individual parameters in both 8bit and 16bit resolution are controlled and displayed on a single grandMA console, with a maximum of 64 discrete DMX universes on the network. When configured in parameter expansion mode, the master console functions as a terminal interface: communicating and displaying locally – while all controlled parameters are processed externally by Network Signal Processors (NSPs).

Multi User

With its unique multi-user functionality, up to 16 consoles, offline applications like onPC, or grandMA 3D visualizer can be linked together on a network to control a single show. Multiple operators can work simultaneously without getting in each other's way and with no need to merge their show files together afterwards. Each individual console can be operated independently.

Wireless Remote Control

Up to six PDAs can function simultaneously as independent wireless remotes in the grandMA system. They can be used for remote focusing, cue editing, or even control of the complete show.

Accessory PC Software

- grandMA 3D (real-time visualization software)
- grandMA onPC (optimised for live control)
- grandMA remote (for Pocket PC remotes)
- grandMA video (media server application; integrates control and programming of video into the console)
- MA 2Port Node Flush-mounted or Rig-mounted version



©2008 MA Lighting International GmbH

Version No. VIII.01 All technical specifications are subject to change without notification. We do not assume liability for any incorrect information in this data sheet.



MA Lighting International GmbH An der Talle 26-28 33102 Paderborn Germany

Phone +49 5251 688865-10 Fax +49 5251 688865-88

info@malighting.com http://www.malighting.com